

SCIV-O-RING spray



DESCRIPTION:

Gliding fluid for electric cables and couplings of pipes with a rubber ring seal. Product insoluble in water that maintains unchanged in time, its lubricating properties.

HOW TO USE:

Spray uniformly on o-rings, on the surface to be coupled or on the cables to slide. Then proceed with the coupling.

TECHNICAL DATA:

| | |
|--------------------------------------|---------------------------------|
| Appearance | colorless liquid |
| Odor | characteristic |
| Volume of the container | 520 ml |
| Volume of the product | 400 ml |
| Operating temperature | -50 ÷ +300 °C |
| Viscosity at 25 °C | 350 cSt |
| Pressure at 20 °C | 3,5 ± 0,3 Bar |
| Test pressure of the cylinder | 15 Bar |
| Relative density of the liquid phase | 0,970 ± 0,005 g/cm ³ |
| Water solubility | insoluble |

PACKAGING:

Spray 400 ml, boxes of 12 pieces.
Bottle 250 g, boxes of 24 pieces.
Bottle 500 g, boxes of 24 pieces.
Tubes 250 g, boxes of 24 pieces.
Cans 500 g, boxes of 18 pieces.

Last update: 19.04.2023



PRODOTTI CHIMICI E TECNICI - CHEMICAL AND TECHNICAL PRODUCTS

FACOT CHEMICALS Srl - Via Crema 44, 26010 Capralba CR, Italy - Tel. +39 0373450642 - info@facot.it - www.facotchemicals.com



CHEMISTRY IN ACTION